

17.5R25

LOAD&CARRY



ALLROUNDREIFEN FÜR DEN
RADLADER- UND GRADEREINSATZ



Dimen.	Felge	Maße (unbelad.)		Radius (belad.)	Abrollumfang	Tragf. Index	Off-the-Road					Schwerer Einsatz			
		B	D				Druck	Empfohl. Beladg., kg (lbs)				Druck	Empfohl. Beladg., kg (lbs)		
		mm	mm	bar	Stillstand	Geschw., km/h (mph)			bar	Stillstand	Geschw., km/h (mph)				
		in	in			psi	3	6			16	psi	3	6	16

17.5R25 L3	14.00/1.5	445 17.5	1345 53	594 23.4	3920 154.3	** 176A2	3.5	9810	6930	6130	5210	4.2	11030	8890	8280	7660
							51	21610	15260	13500	11480	61	24300	19580	18240	16870
							4.0	10610	7490	6630	5640	4.8	11930	9610	8950	8290
							58	23370	16500	14600	12420	70	26280	21170	19710	18260
							4.5	11360	8020	7100	6040	5.4	12780	10300	9590	8880
65	25020	17670	15640	13300	78	28150	22690	21120	19560							



WINSTONE
MANUFACTURED BY RODOS