

23.5R25

LOAD&CARRY 2



ALLROUNDREIFEN FÜR DEN
RADLADER- UND DUMPEREINSATZ



Dimen.	Felge	Maße (unbelad.)		Radius (belad.)	Abrollumfang	Tragf. Index	Off-the-Road					Schwerer Einsatz				
		B	D				Druck	Empfohl. Beladg., kg (lbs)			Druck	Empfohl. Beladg., kg (lbs)				
								Geschw., km/h (mph)				Geschw., km/h (mph)				
		mm in	mm in				bar psi	Still-stand	5 3	10 6	25 16	bar psi	Still-stand	5 3	10 6	25 16
23.5R25 EM L-3/E3	19.50/2.5	605 23.8	1611 63.4	732 28.8	4780 188.2	** 185B	3.5	1730	12250	10840	9210	4.2	19510	15720	14630	13550
							51	38190	26980	23880	20290	61	42970	34630	32220	29850
							4.25	19440	13730	12150	10330	4.8	21870	17620	16400	15190
							62	42820	30240	26760	22750	5.1	48170	38810	36120	33460
							4.5	20100	14190	12560	10680	74	22610	18210	16960	15700
							65	44270	31260	27670	23527	5.4	49800	40110	37360	34580
							5.75	23200	16390	14500	12330	6.9	26100	21030	19580	18130
83	51100	36100	31940	27160	100	57490	46320	43130	39930							



WINSTONE
MANUFACTURED BY RODOS