Rösler Tyre Innovators GmbH & Co. KG

Revision date: 19.02.2016

Rösler Polyfill ISO

according to Regulation (EC) No 1907/2006

Print date: 14.03.2016 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

+49 (231) 917078-00

1.1. Product identifier

Softfill ISO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Polyurethane castable elastomer component B for tyrefilling.

1.3. Details of the supplier of the safety data sheet

Company name: Rösler Tyre Innovators GmbH & Co. KG

Street: Ezzestr.5

Place: D-44379 Dortmund
Telephone: +49 (0)231 917078-00

Telephone: +49 (0)231 917078-00 Telefax:+49 (0)231 917078-12

e-mail: <u>roesler@roesler-tyres.com</u>

1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1

Carcinogenicity: Carc. 1B Reproductive toxicity: Repr. 2 Reproductive toxicity: Lact.

Specific target organ toxicity - repeated exposure: STOT RE 1 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging the unborn child. May cause harm to breast-fed children.

Causes damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Extracts (petroleum), light paraffinic distillate solvent

Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator residue distn.

GB - EN

4,4'-Methylenediphenyl diisocyanate, oligomers

Extracts (petroleum), light paraffinic distillate solvent

alkanes, C14-17, chloro; chlorinated paraffins, C14-17

Formaldehyde, oligomeric reaction products with aniline and phosgene

Signal word: Danger



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 2 of 13

Pictograms:





Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H361d Suspected of damaging the unborn child. H362 May cause harm to breast-fed children.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Revision date: 19.02.2016



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 3 of 13

Hazardous components

| CAS No | Chemical name | | | | | |
|------------|--|--------------------------------------|------------------|-------------|--|--|
| | EC No | Index No | REACH No | | | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | | | |
| 64742-05-8 | Extracts (petroleum), light paraffir | nic distillate solvent | | 25 - < 50 % | | |
| | 265-104-2 | 649-003-00-4 | | | | |
| | Carc. 1B, Repr. 2, STOT RE 1, A | quatic Chronic 2; H350 H361d H37 | 2 H411 EUH066 | | | |
| 68478-13-7 | Heavy Fuel oil, Residues (petrole | um), catalytic reformer fractionator | residue distn. | 10 - < 25 % | | |
| | 270-792-2 | 649-025-00-4 | | | | |
| | Carc. 1B, Aquatic Chronic 2; H35 | 0 H411 | • | | | |
| 25686-28-6 | 4,4'-Methylenediphenyl diisocyan | ate, oligomers | | 10 - < 25 % | | |
| | 500-040-3 | | 01-2119457013-49 | | | |
| | Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373 | | | | | |
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | | | | | |
| | 265-104-2 | 649-003-00-4 | | | | |
| | Carc. 1B, Repr. 2, STOT RE 1, Aquatic Chronic 3; H350 H361d H372 H412 EUH066 | | | | | |
| 85535-85-9 | alkanes, C14-17, chloro; chlorinated paraffins, C14-17 | | | | | |
| | 287-477-0 | 602-095-00-X | 01-2119519269-33 | | | |
| | Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066 | | | | | |
| 32055-14-4 | Formaldehyde, oligomeric reaction products with aniline and phosgene | | | | | |
| | 500-079-6 | | 01-2119457024-46 | | | |
| | Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373 | | | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Revision date: 19.02.2016



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 4 of 13

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

In case of fire: Formation of:

Nitrogen oxides (NOx), Sulphur dioxide (SO2), Carbon dioxide (CO2), Carbon monoxide.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. storage temperature: 20°C

Advice on storage compatibility

Keep away from: Oxidising agent, strong

7.3. Specific end use(s)

Polyurethane castable elastomer component B for tyrefilling.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 5 of 13

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|-----------|---|-----|-------|-----------|---------------|--------|
| 7783-06-4 | Hydrogen sulphide | 5 | 7 | | TWA (8 h) | WEL |
| | | 10 | 14 | | STEL (15 min) | WEL |
| - | Isocyanates, all (as -NCO) Except methyl isocyanate | - | 0.02 | | TWA (8 h) | WEL |
| | | - | 0.07 | | STEL (15 min) | WEL |

DNEL/DMEL values

| CAS No | Substance | | | | |
|-------------|---|----------------|----------|-----------------------|--|
| DNEL type | | Exposure route | Effect | Value | |
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | | | | |
| Worker DNEL | , long-term | dermal | systemic | 1 mg/kg bw/day | |
| 85535-85-9 | alkanes, C14-17, chloro; chlorinated paraffins, C14-17 | | | | |
| Worker DNEL | , long-term | inhalation | systemic | 6,7 mg/m ³ | |
| Worker DNEL | long-term | dermal | systemic | 47,9 mg/kg bw/day | |
| Consumer DN | EL, long-term | inhalation | systemic | 2 mg/m³ | |
| Consumer DN | EL, long-term | dermal | systemic | 28,75 mg/kg bw/day | |
| Consumer DN | EL, long-term | oral | systemic | 0,58 mg/kg bw/day | |

PNEC values

| CAS No | Substance | | | | |
|-----------------------|---|-----------|--|--|--|
| Environmental | Environmental compartment Value | | | | |
| 85535-85-9 | 85535-85-9 alkanes, C14-17, chloro; chlorinated paraffins, C14-17 | | | | |
| Freshwater 0,001 mg/l | | | | | |
| Marine water 0,000 | | | | | |
| Freshwater se | 13 mg/kg | | | | |
| Marine sediment | | 2,6 mg/kg | | | |

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 6 of 13

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material:

NBR (Nitrile rubber), e.g. type Tricotril, article nr. 736 from KCL (www.kcl.de).

CR (polychloroprene, chloroprene rubber), e.g. Camapren, article nr. 720 from KCL (www.kcl.de).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: Mineral oil

Test method

Revision date: 19.02.2016

pH-Value: not determined

Changes in the physical state

Melting point: $-25\,^{\circ}\mathrm{C}$ Initial boiling point and boiling range: not determined Flash point: $>150\,^{\circ}\mathrm{C}$

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined
Ignition temperature: > 240 °C

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: not determined

Density: 1,025 - 1,045 g/cm³

Water solubility: insoluble

Solubility in other solvents

Soluble in: Ketone; Alcohol; Hydrocarbons, aliphatic

Partition coefficient: not determined Viscosity / dynamic: 450 - 750 mPa·s Vapour density: not determined Evaporation rate: not determined Solvent content: 25 - 35 %, water: < 0,05 %

Rösler Tyre Innovators GmbH & Co. KG

Revision date: 19.02.2016

according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 7 of 13

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Danger of polymerisation.

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

Keep away from: Radical former, Peroxide, Reducing agent.

10.6. Hazardous decomposition products

Hydrogen cyanide (hydrocyanic acid).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 8 of 13

| CAS No | Chemical name | | | | |
|------------|---|----------------|---------------------|---------|--------------|
| | Exposure routes | Method | Dose | Species | Source |
| 64742-05-8 | Extracts (petroleum), light paraffin | c distillate s | olvent | | |
| | oral | LD50 | > 5000 mg/kg | Rat | Manufacturer |
| | dermal | LD50 | > 3000 mg/kg | Rabbit | Manufacturer |
| | inhalative (4 h) aerosol | LC50 | > 5 mg/l | Rat | Manufacturer |
| 25686-28-6 | 4,4'-Methylenediphenyl diisocyana | te, oligomer | 's | | |
| | oral | LD50 | > 5000 mg/kg | Rat | OECD 425 |
| | dermal | LD50 | > 9400 mg/kg | Rabbit | OECD 402 |
| | inhalative vapour | ATE | 11 mg/l | | |
| | inhalative aerosol | ATE | 1,5 mg/l | | |
| 64742-05-8 | -05-8 Extracts (petroleum), light paraffinic distillate solvent | | | | |
| | oral | LD50 | > 5000 mg/kg | Rat | OECD 401 |
| | dermal | LD50 | > 3000 mg/kg | Rabbit | OECD 402 |
| | inhalative (4 h) aerosol | LC50 | > 5 mg/l | Rat | OECD 403 |
| 85535-85-9 | alkanes, C14-17, chloro; chlorinate | ed paraffins, | C14-17 | | |
| | oral | LD50 | > 4000 mg/kg | Rat | IUCLID |
| | inhalative (1 h) vapour | LC50 | 48 mg/l | Rat | IUCLID |
| 32055-14-4 | Formaldehyde, oligomeric reaction | products w | rith aniline and pl | nosgene | |
| | oral | LD50 mg/kg | > 10000 | Rat | OECD 401 |
| | dermal | LD50 | > 9400 mg/kg | Rabbit | OECD 402 |
| | inhalative vapour | ATE | 11 mg/l | | |
| | inhalative aerosol | ATE | 1,5 mg/l | | |

Irritation and corrosivity

Causes serious eye irritation.

Causes skin irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4,4'-Methylenediphenyl diisocyanate, oligomers), (Formaldehyde, oligomeric reaction products with aniline and phosgene)

May cause an allergic skin reaction. (4,4'-Methylenediphenyl diisocyanate, oligomers), (Formaldehyde, oligomeric reaction products with aniline and phosgene)

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Causes damage to organs through prolonged or repeated exposure. (Extracts (petroleum), light paraffinic distillate solvent), (Extracts (petroleum), light paraffinic distillate solvent)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (Extracts (petroleum), light paraffinic distillate solvent), (Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator residue distn.), (Extracts (petroleum), light paraffinic distillate solvent)

Suspected of damaging the unborn child. (Extracts (petroleum), light paraffinic distillate solvent), (Extracts (petroleum), light paraffinic distillate solvent)

May cause harm to breast-fed children. (alkanes, C14-17, chloro; chlorinated paraffins, C14-17)

Aspiration hazard

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 9 of 13

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| CAS No | Chemical name | | | | | |
|------------|---|-------------------|---------------------|-----------|--|--------------|
| | Aquatic toxicity | Method | Dose | [h] [d] | Species | Source |
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | | | | | |
| | Acute fish toxicity | LC50 | > 1000 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) | Manufacturer |
| | Acute algae toxicity | ErC50 | 18,8 mg/l | 72 h | Selenastrum capricornutum | Manufacturer |
| | Acute crustacea toxicity | EC50 | 35,9 mg/l | 48 h | Daphnia magna (Big water flea) | Manufacturer |
| 25686-28-6 | 4,4'-Methylenediphenyl diiso | ocyanate, olig | omers | | | |
| | Acute fish toxicity | LC50 | > 3000 mg/l | 96 h | Oryzias latipes (Ricefish) | IUCLID |
| | Acute algae toxicity | ErC50 | > 1640 mg/l | 72 h | Desmodesmus subspicatus. | OECD 201 |
| 64742-05-8 | Extracts (petroleum), light p | araffinic distill | ate solvent | | | |
| | Acute fish toxicity | LC50 | > 1000 mg/l | 96 h | Oncorhynchus mykiss (Rainbow trout) | OECD 203 |
| | Acute algae toxicity | ErC50 | 18,8 mg/l | 72 h | Selenastrum capricornutum | OECD 201 |
| | Acute crustacea toxicity | EC50 | 35,9 mg/l | 48 h | Daphnia magna (Big water flea) | OECD 202 |
| 85535-85-9 | alkanes, C14-17, chloro; chl | orinated para | ffins, C14-17 | | | |
| | Acute algae toxicity | ErC50 | > 3,2 mg/l | 96 h | Selenastrum capricornutum | OECD 201 |
| 32055-14-4 | Formaldehyde, oligomeric re | eaction produ | cts with aniline ar | nd phos | gene | |
| | Acute fish toxicity | LC50 | > 3000 mg/l | 96 h | Oryzias latipes (Ricefish) | IUCLID |
| | Acute algae toxicity | ErC50 | > 1640 mg/l | 72 h | Desmodesmus subspicatus. | OECD 201 |

12.2. Persistence and degradability

The product has not been tested.

| CAS No | Chemical name | | | | | |
|------------|---|-------|----|--------|--|--|
| | Method | Value | d | Source | | |
| | Evaluation | | | | | |
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | | | | | |
| | EU Method C.4-E | 0 | 28 | ECHA | | |
| | Poorly biodegradable. | | | | | |
| 25686-28-6 | 4,4'-Methylenediphenyl diisocyanate, oligomers | | | | | |
| | OECD 302 C | 0% | 28 | | | |
| | Not readily biodegradable (according to OECD criteria) (| | | | | |
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | | | | | |
| | OECD 301D/ EEC 92/69/V, C.4-E | 0% | 28 | | | |
| | Not readily biodegradable (according to OECD criteria) | | | | | |
| 85535-85-9 | alkanes, C14-17, chloro; chlorinated paraffins, C14-17 | | | | | |
| | OECD 301D/ EEC 92/69/V, C.4-E | 64% | 28 | | | |
| | Readily biodegradable (according to OECD criteria). | | | | | |
| 32055-14-4 | -4 Formaldehyde, oligomeric reaction products with aniline and phosgene | | | | | |
| | OECD 302 C | 0% | 28 | | | |
| | Not readily biodegradable (according to OECD criteria) (| | | | | |

Rösler Tyre Innovators GmbH & Co. KG

according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 10 of 13

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---|---------|
| 64742-05-8 | Extracts (petroleum), light paraffinic distillate solvent | > = 4 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|--|-------------|--|------------|
| 25686-28-6 | 4,4'-Methylenediphenyl diisocyanate, oligomers | 92-200 | Cyprinus carpio (Common Carp) | OECD 305 E |
| 85535-85-9 | alkanes, C14-17, chloro; chlorinated paraffins, C14-17 | 3050 - 6660 | Oncorhynchus mykiss (Rainbow trout) | OECD 305 |
| 32055-14-4 | Formaldehyde, oligomeric reaction products with aniline and phosgene | 92-200 | Cyprinus carpio (Common Carp) | OECD 305 E |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator

residue distn.)

9 III

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:



Classification code: M6

Special Provisions: 274 335 601

Limited quantity: 5 L Transport category: 3



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 11 of 13

Hazard No: 90
Tunnel restriction code: E

Other applicable information (land transport)

Excepted quantity: E1

Inland waterways transport (ADN)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator

residue distn.)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code: M6

Special Provisions: 274 335 601

Limited quantity: 5 L

Other applicable information (inland waterways transport)

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator

residue distn.)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: 274, 335 Limited quantity: 5 L EmS: F-A, S-F

Other applicable information (marine transport)

Excepted quantity: E1

Air transport (ICAO)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator

residue distn.)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158



according to Regulation (EC) No 1907/2006

Rösler Polyfill ISO

Print date: 14.03.2016 Page 12 of 13

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

Excepted quantity: E1 Passenger-LQ: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Revision date: 19.02.2016

Danger releasing substance: Heavy Fuel oil, Residues (petroleum), catalytic reformer fractionator residue

distn.

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work

protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 3 - highly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,12,13,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Revision date: 19.02.2016



Safety Data Sheet

according to Regulation (EC) No 1907/2006

| Rösler Polyfill ISO | | | | |
|---|--|---------------|--|--|
| Print date: 14.03.2016 | | Page 13 of 13 | | |
| H332 H334 H335 H350 H351 H361d | Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Suspected of causing cancer. Suspected of damaging the unborn child. | | | |
| H362 H372 H373 H400 H410 | May cause harm to breast-fed children. Causes damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. | | | |
| H412 EUH066 EUH204 | Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Contains isocyanates. May produce an allergic reaction. | | | |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)